



Note: Overall Lengths over 53'-0" may require special permitting

Specifications

Capacity	100,000 lbs.
Weight	22,500 lbs.
Axles	(3) Dana 25,000 lb. Each
Suspension	(3) 25,000 lbs. Air Ride
Brakes	(6) 16 1/2" x 7" Air
ABS	4S2M All Wheels with Spring Brakes (NO Spring Brakes on Flip)
Wheels	(12) 10-stud 8.25 x 22.5 Hub Piloted Hubs and Wheels
Tires	(12) 255/70R22.5 H Steel Radials

Features

- * Pierced crossmembers
- * 100,000 lb. Min. T-1 Steel Mainframe
- * Sealed Modular Wiring and "LED" Lights
- * (7) Roto Rings swivels 360° per side
- * 2" Nominal Apitong decking * NO Center Boards
- * 20" (loaded) Deck Ht with 18" Cossmember Spacing
- * Mud Flaps * Manual Raise & Lower Valve
- * 50"/98" Swing, 4" Relief G/Neck (13hp Honda Combo)
- * Standard Boomwell * Steel Front Flip Ramps with Grousers
- * Color- Standard Eager Beaver White
- * Wheelcovers * 56"/56" Axle Spacings
- * Flip 3rd Axle with Wheelcovers * Flip 3rd Axle to be Setup for Flip 4th Axle

50-GSL/3

50 ton Detachable Air Ride with
Flip Third Axle

Prepared for:	10167.dwg	Date: 07-11-06	LAW
---------------	-----------	----------------	-----

Eager Beaver
Trailers

14983 Hwy. 27 South
Lake Wales, FL 33859
800-257-8163

This drawing and specifications are the property of General Engines Co, Inc. They shall not be reproduced, copied or used as the bases for the manufacture or sale of apparatus or devices without permission. Also, General Engines Co., Inc., in accordance with our established policy of constant improvement, reserves the right to amend these specifications at any time without notice.