



Specifications

- Capacity 110,000 lbs.
- Weight 23,000 lbs. without Flip
26,000 lbs. with Flip
- Axles (4) Dana 25,000 lb. Each
- Suspension (4) 25,000 lbs. Air Ride Each
- Brakes (8) 16 1/2" x 7" Air
- ABS 4S3M All Wheels with Spring brakes
- Wheels (16) 10-stud 8.25 x 22.5 Hub Piloted
- Tires (16) 275/70R22.5 H Steel Radials

Features

- * Pierced crossmembers
- * 80,000 lb. Min. Yield Steel Mainframe
- * Sealed Modular Wiring and "LED" Lights
- * (7) Roto Rings swivels 360° per side (STD)
- * Lift 3rd Axle * Mud Flaps
- * 2" Nominal Apitong decking * 26' Flat Deck
- * Flip 4th Axle * 54"/54" Axle Spacings
- * Steel Front Flip Ramps w/Grousers
- * 50"/82" & 98" Dual Swing G/Neck, (13HP Honda Powerpack)
- * Color- Standard Black
- * Std. Boomwell

55GSL/3
55ton Detachable Air Ride with
Lift 3rd & Flip 4th Axle

Prepared for: 10284.dwg | Date: 02-27-06 | LAW
Equipment Sales

14983 Hwy. 27 South
Eager Beaver Lake Wales, FL 33859
 800-257-8163

This drawing and specifications are the property of General Engines Co., Inc. They shall not be reproduced, copied or used as the bases for the manufacture or sale of apparatus or devices without permission. Also, General Engines Co., Inc., in accordance with our established policy of constant improvement, reserves the right to amend these specifications at any time without notice.