



Specifications

Trailer:
 Capacity 120,000 lbs.
 Weight 24,250 lbs. w/o Flip Axle
 Axles (3) Hendrickson 25,000 lb. Each
 Suspension (3) 25,000 lbs. Air Ride
 Brakes (6) 16 1/2" x 7" Air
 ABS 4S3M Wabco w/ spring brakes
 Wheels (12) Disk type 10 hole hub piloted
 Tires (12) 275/70R22.5 H Steel Radials

Jeep:
 Capacity 100,000 lbs.
 Weight 12,000 lbs.
 Axles (2) Hendrickson 25,000 lb. Each
 Suspension (2) 25,000 lbs. Air Ride
 Brakes (4) 16 1/2" x 7" Air
 Wheels (8) Disk type 10 hole hub piloted
 Tires (8) 275/70R22.5 H Steel Radials

Spreader Bar: Express Welding Nitro-Booster
 Capacity 25,000 lbs.
 Weight 4,500 lbs.
 Axles (1) Hendrickson 25,000 lb. Each
 Suspension (1) 25,000 lbs. Air Ride
 Brakes (2) 16 1/2" x 7" Air
 Wheels (4) Disk type 10 hole hub piloted
 Tires (4) 275/70R22.5 H Steel Radials

Features

- * Pierced crossmembers
- * 24'-6" Flat Deck
- * 100,000 PSI Min. Yield Steel (T-1) Mainframe
- * Sealed Modular Wiring and "LED" Lights
- * (7) Roto Rings swivels 360° per side
- * 2" Nominal Hardwood decking
- * 50" Gooseneck Ht, Dual Removable Kingpins, 102" & 114" Swing Clearance
- * 13hp Honda Powerpack
- * Steel Front Flip Ramps with Grouser
- * Std. Boomwell * Lift 3rd Axle
- * 60/60 Axle Spacings * Std. Mud Flaps
- * Complete Set-UP for Flip 4th Axle & Nitro-Booster
- * Color- E.B. Yellow , Red, or Black
- * (2) Axle Jeep -
 50" GN Ht, 82" Swing
 Adjustable Sliding SAF-Holland Fithwheel
 Air Ride Suspension

NOTE: OVERALL LENGTHS OVER 53' 0" MAX MAY REQUIRE SPECIAL PERMITTING

60GSL/3

**60 ton Detachable Air Ride
 with Lift 3rd Axle
 4th Axle Nitro-Booster
 and Two Axle Air Ride Jeep**

Prepared for: 10437.dwg Rev-02 Date: 05-16-08 FMc

Darlings & Sons

14893 Hwy. 27 South
 Lake Wales, FL 33859
 1-800-257-8163

Eager Beaver Trailers

This drawing and specifications are the property of General Engines Co., Inc. They shall not be reproduced, copied or used as the bases for the manufacture or sale of apparatus or devices without permission. Also, General Engines Co., Inc., in accordance with our established policy of constant improvement, reserves the right to amend these specifications at any time without notice.