



Specifications

Trailer:
 Capacity 130,000 lbs. (in 13'-0" area)
 Weight 29,000 lbs. (Trailer Only)
 Axles (3) Hendrickson 25,000 lb. Each
 Suspension (3) 25,000 lbs. Air Ride
 Brakes (6) 16 1/2" x 7" Air
 ABS 4S3M Wabco w/ spring brakes
 Wheels (12) Disk type 10 hole hub piloted
 Tires (12) 275/70R22.5 H Steel Radials

Jeep:
 Capacity 100,000 lbs.
 Weight 8,500 lbs.
 Axles (2) Hendrickson 25,000 lb. Each
 Suspension (2) 25,000 lbs. Air Ride
 Brakes (4) 16 1/2" x 7" Air
 Wheels (8) Disk type 10 hole hub piloted
 Tires (8) 275/70R22.5 H Steel Radials

Tandem Axle Spreader Bar with (2) Interim Flips:
 Capacity 50,000 lbs.
 Weight 2,500 lbs. (Sreader Bar)
 2,555 lbs. (each Flip)
 Axles (2) Hendrickson 25,000 lb. Each
 Suspension (2) 25,000 lbs. Air Ride
 Brakes (2) 16 1/2" x 7" Air
 Wheels (8) Disk type 10 hole hub piloted
 Tires (8) 275/70R22.5 H Steel Radials

Features

- * Pierced crossmembers
- * 26'-0" x 10'-0" Flat Deck, Full Width Axles
- * 100,000 PSI Min. Yield Steel (T-1) Mainframe
- * Sealed Modular Wiring and "LED" Lights
- * (7) Roto Rings swivels 360° per side
- * Nominal 2" Apitong Decking
- * 50" Gooseneck Ht, 114" Swing Clearance
- * 13hp Honda Combo * 5' GN Extension with hydraulic assist
- * Steel Front Flip Ramps with Grouser
- * Std. Boomwell * Lift 3rd Axle
- * 60/60 Axle Spacings * Std. Mud Flaps
- * Complete Set-Up for Flip 4th & 5th Axle and Tandem Spreader Bar
- * Color- E.B. Yellow , Red, or Black
- * (2) Axle Jeep - 50" GN Ht, 82" & 102" Dual Swing, Adjustable Sliding SAF-Holland Fithwheel and Air Ride Suspension

Note: Trailer lengths over 53'-0" may require special permitting

65-GSL/3

**65 ton Detachable Air Ride
 10'-0" Wide with Lift 3rd Axle
 4th & 5th Axle East Coast Booster
 and Two Axle Air Ride Jeep**

Prepared for: 10626.dwg Date: 03-19-09 LAW

Equipment Sales



14893 Hwy. 27 South
 Lake Wales, FL 33859
 1-800-257-8163

This drawing and specifications are the property of General Engines Co, Inc. They shall not be reproduced, copied or used as the bases for the manufacture or sale of apparatus or devices without permission. Also, General Engines Co., Inc., in accordance with our established policy of constant improvement, reserves the right to amend these specifications at any time without notice.